

Product Code	HID-24W-B HID-24W-S	HID-3528-4400-B HID-3528-4400-S	HID-5038-B HID-5038-S
			
A total Set (HID flashlight & Accessories)	1) HID Flashlight body; 2) Battery; 3) Indoor battery charger adaptor portable car charger; 4) amber filter; 5) Flashlight belt clip; 6) hand-held aluminium carrying box 7) mirror brushing fabric 8)	1) HID Flashlight body; 2) Battery; 3) Indoor battery charger adaptor portable car charger; 4) amber filter; 5) Flashlight belt clip; 6) hand-held aluminium carrying box 7) mirror brushing fabric 8)	1) HID Flashlight body; 2) Battery; 3) Indoor battery charger adaptor portable car charger; 4) amber filter; 5) Flashlight belt clip; 6) hand-held aluminium carrying box 7) mirror brushing fabric 8)
Bulb Type	HID (High Intensity Discharge) Lamp	HID (High Intensity Discharge) Lamp	HID (High Intensity Discharge) Lamp
Power and voltage	24W/12V	35W/28W, 12V	50W/38W, 12V
Lumen	1440LM	3400LM(at 5000K) · 3800-4300LM(6000K-8000K)/35W	4500LM
Color	Black & Silver	Black & Silver	Black & Silver
Battery type	2200mAH	4400mAH /6600mAH	6600mAH
Continual illuminate time	60Min(2200mAH)	105min/35w, 140min/28w(6600mAH); 70min/35w, 90min/28w(4400mAH)	100min/38w, 70min/50w(6600mAH)
Bright color temperature	6000K(standard)	5000K(standard)	6000K(standard)
Irradiation distance	800M	1000M	1500M
Bulb life span	3000hrs	>3000hrs	>3000hrs
Dimension	L:230mm · Head:φ71mm,Torch:φ41mm	L:386mm · Head:φ88mm,Torch:φ46mm	L:386mm · Head:φ88mm,Torch:φ46mm
Battery life span	>500 times	>500 times	>500 times
WaterProofness	IPX3	IPX3	IPX3
Material	Aluminium alloy	Aerospace-Grade Aluminium alloy (6061 T6)	Aerospace-Grade Aluminium alloy (6061 T6)
Packing Size &Gross Weight	26.5*17.2*9.5CM, 1.78kg/set	42X23X12.5CM, 3.3KG/set	42X23X12.5CM, 3.3KG/set
Carton Package	31.5*20.2*50.5CM, 5pcs/carton, 10KG	53.5X44X47CM,8pcs/carton, 27KG	53.5X44X47CM,8pcs/carton, 27KG